

2014

LE ROUTE 2 2014 (ONLY SMALL SIZE)



SPECS

FRAME	New 2014 LE ROUTE disc, alloy 6061 smooth welded
SHOCK	-
FORK	LE ROUTE alloy disc fork
HEADSET	NECO 1 1/8 integrated, campy style, sealed bearings
STEM	RIDE ALPHA, alloy 6061 forged, 70mm, 0° rise, ø31,8mm
BAR	COMMENCAL ø31,8mm, alloy 6061, 1 1/8rise, 600mm
GRIPS	New COMMENCAL 2014, outside ø32mm, soft compound
BRAKES	TEKTRO HDC330 hydraulic disc brake 160mm/160mm, with reach adjustment
SHIFTERS	SRAM x7 2x10 speed
FRONT / REAR MECH	SRAM apex ø34.9 2 speed / SRAM x7 10 speed
BOTTOM BRACKET	SRAM GX P 68mm, sealed bearings
CRANKSET	SRAM apex 48/34t
CHAIN	YABAN SH10C, with quick link connector
CASSETTE	SRAM PG1050 12-36t
RIMS	JALCO disc 700C 24h
HUBS	JOYTECH disc 24h front, sealed bearings, qr version
SPOKES	Stainless butted steel black, 24 radial front, 28 semi radial rear
TIRES	VITTORIA rubino 700x28C
SEATPOST	COMMENCAL alloy no offset, ø27,2mm, one piece design, 350mm
SADDLE	COMMENCAL LE ROUTE by Velo, CrMo rails, soft padding
PEDALS INCLUDED	No

TECH

BICYCLE TYPE	Road Bicycle
FRAMLE MATERIAL	NEC + ULTRA SL (Aluminium 6061) Triple Butted
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK SPACER DIMENSION	-
RECOMMENDED / MAX FORK HEIGHT	380mm / 390mm
HEADSET DIMENSION	1 1/8"
HEADSET TYPE	Integrated headset type Campa 45° / 45°
MAXIMUM TYRE WIDTH (ETRTO)	28mm
DISC BRAKE STANDARD	International Standard
REAR ROTOR MAX SIZE	160 mm
SEATPOST / SEAT CLAMP DIAMETER	27,2mm / 30,6 mm
BOTTOM BRACKET TYPE	68mm BSA
ISCG	Not compatible
FRONT DERAILLEUR	Down swing 34,9mm - down pull
REAR HUB COMPATIBILITY	130x10mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	280 mm	284 mm
REAR	281 mm	280 mm