

2014

COMMENCAL META HT CRMO 650B 2014



SPECS

FRAME	New 2014 META CRMO 650b, CrMo light double butted, integrated hanger
SHOCK	-
FORK	FOX 32 650b float evolution o/c, 150mm qr15
HEADSET	semi integrated, tapered zs44/44, 1 1/8 lower washer ball retainer
STEM	RIDE ALPHA, alloy 2014 forged, 60mm, 0° rise, ø31,8mm
BAR	RIDE ALPHA, alloy 6061db, 0.75 rise, 750mm, ø31,8mm
GRIPS	COMMENCAL 2014 lock on, outside ø30mm, soft compound
BRAKES	New FORMULA C1, 180mm/180mm, with X7 matchmaker
SHIFTERS	SRAM x7 2x10 speed
FRONT / REAR MECH	SRAM x5 2 speed / SRAM x7 type 2 10 speed
BOTTOM BRACKET	SRAM GXP 92mm sealed bearings
CRANKSET	SRAM S1000 GXP 24/38t, 170mm xs/s, 175mm m/l/xl
CHAIN	YABAN SH10C, with quick link connector
CASSETTE	SRAM PG1030 11-36t
RIMS	650b 32h double wall, 26,5mm, pin joint, disc version
HUBS	32h, sealed bearings, steel cassette body
SPOKES	Stainless steel 1,8mm black - brass 12mm black, lockseal
TIRES	MAXXIS High Roller II EXO 650bx2,3 front, ardent 650b x 2.25 EXO rear, 60tpi folding bead
SEATPOST	KINDSHOCK ETEN remote, 100mm travel 30,9x385mm
SADDLE	COMMENCAL META, CrMo rails

TECH

BICYCLE TYPE	All Mountain Hardtail
FRAME MATERIAL	New 2014 META CRMO 650b, CrMo light double butted, integrated hanger
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK SPACER DIMENSION	-
RECOMMENDED / MAX FORK HEIGHT	544mm / 555mm
HEADSET DIMENSION	1 1/8" Compatible with a tapered fork
HEADSET TYPE	ZS44 / EC44
MAX TYRE WIDTH (ETRTO)	70mm
DISC BRAKE STANDARD	International Standard 160mm
REAR ROTOR MAX SIZE	185mm
SEATPOST / SEAT CLAMP DIAMETER	30,9mm, integrated seat clamp
MINIMUM SEATPOST INSERT:	12 cm
BOTTOM BRACKET TYPE	68 mm BSA
ISCG	ISCG05
FRONT DERAILLEUR TYPE	Compatible, 34.9 Down Swing
REAR HUB COMPATIBILITY	135X10 mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	269 mm	271 mm
REAR	271 mm	269 mm