

2015

COMMENCAL FCB ESSENTIAL 29 BLACK 2015



SPECS

FRAME	NEW FCB Disc, Alloy 6061 smooth welded, Fenders and rack ready
SHOCK	-
FORK	NEW FCB alloy Disc fork, fenders ready
HEADSET	1 1/8" integrated, campy style, sealed bearings
STEM	RIDE ALPHA, Alloy 6061 forged, 70mm, 0° rise, Ø31,8mm
BAR	RIDE ALPHA, Ø31,8, 640mm, AL6061
GRIPS	COMMENCAL, Ø32mm, SOFT COMPOUND
BRAKES	TEKTRO HDM290 hydraulic disc brake 160mm/160mm, w reach adjustment
SHIFTERS	SRAM X5 2x9 spd
FRONT / REAR MECH	SRAM APEX, 2 speed / SRAM X7, 9 speed, Medium cage
BOTTOM BRACKET	BSA, sealed bearings
CRANKSET	Forged 2 piece, 2x9, 50/34 talloy chainring, 170mm on S, 175mm on M/L/XL
CHAIN	Yaban 9 spd
CASSETTE	SRAM PG950 11-34 t
RIMS	700cc double wall, 32mm profile, 24h, pin joint
HUBS	24H, sealed bearings, disc version
SPOKES	Spoke Stainless Steel 1,8mm black nipple brass 12mm black
TIRES	MAXXIS Refuse 28c, 60 Tpi, Max Shield
SEATPOST	Alloy no offset Ø27,2mm, 350mm
SADDLE	COMMENCAL Urban, steel black rails, soft padding

TECH

BICYCLE TYPE	Road-Urban hardtail bike
FRAMLE MATERIAL	NEC + ULTRA SL (Aluminium 6061) Triple Butted
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK SPACER DIMENSION	-
RECOMMENDED / MAX FORK HEIGHT	450mm
HEADSET DIMENSION	1"1/8
HEADSET TYPE	Integrated headset type Campa 45° / 45°
MAXIMUM TYRE WIDHT (ETRTO)	28mm
DISC BRAKE STANDARD	DBS International
REAR ROTOR MAX SIZE	160mm
SEATPOST / SEAT CLAMP DIAMETER	27,2mm / 30,6 mm
BOTTOM BRACKET TYPE	68mm BSA
ISCG	Not compatible
FRONT DERAILLEUR	Up swing 34,9mm - down pull
REAR HUB COMPATIBILITY	130x10mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	272 mm	274 mm
REAR	274 mm	272 mm