

2015

COMMENCAL SUPREME DH V3 650B WC 2015



SPECS

FRAME	NEW SUPREME DH 650b, Travel 190mm, 7005 alloy hydroformed, light version internal routing
SHOCK	RockShox Vivid Air R2C, 240x76
FORK	RockShox Boxxer World Cup 200mm
HEADSET	Semi integrated, tapered ZS44/56, 1.5" lower washer, sealed bearing
STEM	Renthal Integra direct mount
BAR	Renthal Fatbar, 30mm rise, 780mm, Ø31.8mm
GRIPS	Renthal Lock On Kevlar
BRAKES	SRAM CODE 200mm / 200mm
SHIFTERS	SRAM X0 DH 7s
FRONT / REAR MECH	- / SRAM X01 DH 7s Short Cage Black
BOTTOM BRACKET	RACE FACE Press fit 107, sealed bearing
CRANKSET / CHAIN GUIDE	SRAM X01 DH, 165mm, XSYNC 34t ring / E13 LG1+ Alloy Backplate with Taco
CHAIN	SRAM PC X1
CASSETTE	SRAM PG795 DH, 10-24, 7s
RIMS	RIDE ALPHA DH 32h, 650b, double wall, tubeless ready 31mm sleeved joint, handbuilt
HUBS	RIDE ALPHA 32h sealed bearings, SuperLightSteel freewheel, 20x100 Front / 12x150 Rear
SPOKES	RIDE ALPHA Race 2/1,8/2mm black - brass 14mm black, lockseal handbuilt
TIRES	MAXXIS High Roller II, 27,5x2,40 , 60 TPI, 2 ply, 3C MaxxGrip
SEATPOST	SDG I-Beam 31,6x350mm
SADDLE	SDG I-Fly I-Beam
PEDALS INCLUDED	No

TECH

BICYCLE TYPE	DH, full suspended competition bike
FRAME	NEC + ULTRA XTRM (Aluminium 7005 Triple Butted)
SHOCK TRAVEL	190mm
SHOCK LENGTH / STROKE	241x76mm
PIGGY BACK SHOCK COMPATIBLE	Yes
SHOCK SPACER DIMENSION	22,2x10mm
RECOMMENDED / MAX FORK HEIGHT	585mm / 595mm
HEADSET DIMENSION	Tapered 1.1/8" - 1.5"
HEADSET TYPE	CANE CREEK standard ZS44 / ZS56
MAXIMUM TYRE WIDTH (ETRTO)	75mm
DISC BRAKE STANDARD	International Standard
REAR ROTOR MAXIMUM SIZE	203mm
SEATPOST / SEAT CLAMP DIAMETER	31,6mm / 34,9mm
BOTTOM BRACKET TYPE	Press fit BB107 (compatible BB92)
ISCG	ISCG05
FRONT DERAILLEUR TYPE	Not compatible
REAR HUB COMPATIBILITY	150x12mm