

2016

COMMENCAL FCB 29 RED 2016



SPECS

FRAME	2016 FCB 700c Disc, Alloy 6061 smooth welded, Integrated routing
SHOCK	-
FORK	2016 FCB 700c, Disc mount
HEADSET	Semi cartridge bearings, 1.1/8"
STEM	RIDE ALPHA, Aluminium 2014, 70mm, 31,8mm, 0° Angle
BAR	RIDE ALPHA, 640mm, 20mm rise, aluminium 6061
GRIPS	COMMENCAL, soft compound, Ø32mm
BRAKES	AVID DB3, 2 pistons hydraulic disc brake 160/160mm, with reach adjustment
SHIFTERS	SRAM X7, 2x10 speed
FRONT / REAR MECH	SRAM APEX, 2 speed / SRAM X7, 10 speed, Medium cage
BOTTOM BRACKET	BSA BB 68mm, sealed bearings
CRANKSET	Alloy forged, Hollow axle, 34/50T, 172,5mm on XS/S and 175mm on M/L/XL
CHAIN	KMC X10, 10 speed
CASSETTE	SRAM PG-1020, 11-36T
RIMS	Double Wall, Asymetric profile, 24 holes, pin joint
HUBS	RIDE ALPHA, 24 holes, loose ball bearings
SPOKES	Spoke Stainless Steel 1,8mm black nipple brass 12mm black
TIRES	MAXXIS Refuse 700x28c, 60 Tpi, Foldable, Maxxisshield protection
SEATPOST	RIDE ALPHA, Ø27,2mm, alloy, no offset, 350mm
SADDLE	RIDE ALPHA, Super light foam, Cromo rail
PEDALS INCLUDED	No

TECH

BICYCLE TYPE	Road-Urban hardtail bike
FRAMLE MATERIAL	NEC + ULTRA SL (Aluminium 6061) Triple Butted
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK SPACER DIMENSION	-
RECOMMENDED / MAX FORK HEIGHT	450mm
HEADSET DIMENSION	1"1/8
HEADSET TYPE	Integrated headset type Campa 45° / 45°
MAXIMUM TYRE WIDTH (ETRTO)	28mm
DISC BRAKE STANDARD	DBS International
REAR ROTOR MAX SIZE	160mm
SEATPOST / SEAT CLAMP DIAMETER	27,2mm / 30,6 mm
BOTTOM BRACKET TYPE	68mm BSA
ISCG	Not compatible
FRONT DERAILLEUR	Up swing 34,9mm - down pull
REAR HUB COMPATIBILITY	130x10mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	282 mm	284 mm
REAR	284 mm	282 mm