

2016

COMMENCAL META HT AM ESSENTIAL ROCKSHOX 650B YELLOW 2016



SPECS

FRAME	2016 META HT AM 650B, alloy 6061 triple butted, Top tube hidden cable path, Tapered headtube
SHOCK	-
FORK	ROCK SHOX Yari RC 160, 650b, tapered, travel 160mm, 15mm axle
HEADSET	Semi integrated, tapered ZS44/56, 1 1/8 crown race, semi cartridge
STEM	RIDE ALPHA, Alloy 2014 Forged, 50mm, 0° rise, Ø31,8mm
HANDLEBAR	RIDE ALPHA, Alloy 6061, double butted, 30mm rise, 760mm, Ø31,8mm
GRIPS	COMMENCAL Lock On, Ø32mm, soft compound
BRAKES	SRAM DB1 200mm/180mm
SHIFTERS	SRAM X5 2x9 speed
FRONT / REAR MECH	SRAM X5 high Direct Mount 2 speed / SRAM X7 9 speed
BOTTOM BRACKET	ISIS BB 68mm, sealed bearings
CRANKSET	RIDE ALPHA Forged 2x9, 22/36 t, 170mm on S/M, 175mm on L/XL
CHAIN	YBN 9 speed
CASSETTE	SRAM PG920 11-34 T
RIMS	RIDE ALPHA 650b 32H Double Wall, Tubeless Ready
HUBS	RIDE ALPHA 32h, loose ball light version, light Quick Release skewer
SPOKES	Pillar Spokes 2.0mm (Nylock)
TYRES	MAXXIS Minion DHR II 2.3 EXO, Dual compound, 60 Tpi. Tubeless Ready
SEATPOST	KIND SHOCK Eten, 100 mm travel
SADDLE	RIDE ALPHA SuperLight foam, CrMo rails.
PEDALS INCLUDED	No

TECH

BICYCLE TYPE	All Mountain Hardtail
FRAME MATERIAL	Aluminium 6061 Triple Butted
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK SPACER DIMENSION	-
RECOMMENDED / MAX FORK HEIGHT	530 mm / 544 mm
HEADSET DIMENSION	Tapered 1 1/8" / 1.5"
HEADSET TYPE	Semi-integrated ZS44 / ZS56
MAXIMUM TYRE WIDTH (ETRTO)	60mm
DISC BRAKE STANDARD	International Standard
REAR ROTOR MAX SIZE	185mm
SEATPOST / SEAT CLAMP DIAMETER	31,6mm / 34,9mm
MINIMUM SEATPOST INSERT:	12 cm
BOTTOM BRACKET TYPE	68mm BSA
ISCG	No
FRONT DERAILLEUR TYPE	High direct mount
REAR HUB COMPATIBILITY	135x10mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	271 mm	274 mm
REAR	273 mm	273 mm