

2016

COMMENCAL META HT AM RACE 650B RED 2016



SPECS

FRAME	2016 META HT AM 650B, alloy 6061 triple butted, Top tube hidden cable path, Tapered headtube
SHOCK	-
FORK	ROCKSHOX Pike RC, 27,5", Solo Air, Travel 160mm, 15mm tapered
HEADSET	Semi integrated, tapered ZS44/56, 1.5 crown race, sealed bearing, alloy cups
STEM	RIDE ALPHA, Alloy 2014 Forged, 50mm, 0° rise, Ø31,8mm
BAR	RIDE ALPHA, Alloy 7075, double butted, 30mm rise, 780mm, Ø31,8mm
GRIPS	COMMENCAL Lock On, Ø32mm, soft compound
BRAKES	SRAM DB5, 200mm/180mm, with Matchmaker
SHIFTERS	SRAM X7 1x10 speed
FRONT / REAR MECH	- / SRAM X9 10 speed, type 2.1
BOTTOM BRACKET	BSA 68mm, sealed bearings
CRANKSET	RIDE ALPHA Forged 1x10, RIDE ALPHA narrow wide 32T chainring 170mm on S/M, 175mm on L/XL
CHAINE	KMC X10 10 speed
CASSETTE	SRAM PG1020 11-36 t + Extra cog 42T ALPHA (including 16T cog)
RIMS	RIDE ALPHA 650b 32H double wall, Tubeless Ready
HUBS	RIDE ALPHA 32h, loose ball, light Quick Release skewer
SPOKES	Pillar Spokes 2.0mm (Nylock)
TIRES	MAXXIS Minion DHR II 2.3 front and rear. EXO, Dual compound, 60 Tpi. Tubeless Ready
SEATPOST	KS Eten, 100mm travel
SADDLE	RIDE ALPHA SuperLight foam, CrMo rails. Neon Red
PEDALS INCLUDED	No

TECH

BICYCLE TYPE	All Mountain Hardtail
FRAME MATERIAL	Aluminium 6061 Triple Butted
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK SPACER DIMENSION	-
RECOMMENDED / MAX FORK HEIGHT	530mm / 544mm
HEADSET DIMENSION	Tapered 1"1/8, 1/5"
HEADSET TYPE	Semi-integrated ZS44 / ZS56
MAX TYRE WIDTH (ETRTO)	60mm
DISC BRAKE STANDARD	International Standard
REAR ROTOR MAX SIZE	185mm
SEATPOST / SEAT CLAMP DIAMETER	31,6mm / 34,9mm
MINIMUM SEATPOST INSERT	12 cm
BOTTOM BRACKET TYPE	68mm BSA
ISCG	No
FRONT DERAILLEUR TYPE	High Direct Mount
REAR HUB COMPATIBILITY	135x10mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	271 mm	274 mm
REAR	273 mm	273 mm