

2016

COMMENCAL META HT TRAIL 29 RED 2016



SPECS

FRAME	2016 META HT Trail 29 Alloy 6061 triple butted, Top tube hidden cable path, tapered headtube
SHOCK	-
FORK	ROCKSHOX XC30 GOLD, 100mm Travel, 9 mm axle
HEADSET	Semi integrated,tapered ZS44/56, 1 1/8 crown race, semi cartridge bearings
STEM	RIDE ALPHA, Alloy 2014 Forged, 70mm, 0° rise, Ø31,8mm
BAR	RIDE ALPHA, Alloy 6061, 20mm rise, 720mm, Ø31,8mm
GRIPS	COMMENCAL Lock On, Ø32mm, soft compound
BRAKES	AVID DB1 180mm/160mm
SHIFTERS	SRAM X5 2x9 speed
FRONT / REAR MECH	SRAM X5 high direct mount 2 speed / SRAM X7 9 speed, medium cage
BOTTOM BRACKET	ISIS BB 68mm, sealed bearings
CRANKSET	RIDE ALPHA Forged 2x9, 22/36 T, 170mm on S, 175mm on M/L/XL
CHAIN	YBN 9 speed
CASSETTE	SRAM PG920 11-34 T
RIMS	RIDE ALPHA 29 32H Double Wall
HUBS	RIDE ALPHA 32h, loose ball light version, light Quick Release skewer
SPOKES	Spoke steel 1,8mm black - nipple brass 12mm black
TIRES	MAXXIS Ardent 2.25 front and Ikon 2.2 rear 60 Tpi
SEATPOST	RIDE ALPHA Alloy No offset, Ø31,6mm, 350mm
MINIMUM SEATPOST INSERT:	12 cm
SADDLE	RIDE ALPHA SuperLight foam, CrMo rails. Neon Red
PEDALS INCLUDED	No

TECH

BICYCLE TYPE	Trail / XC Hardtail
FRAME MATERIAL	NEC + ULTRA SL (Aluminium 6061 triple butted)
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK SPACER DIMENSION	-
RECOMMENDED / MAX FORK HEIGHT	506mm / 526mm
HEADSET DIMENSION	Tapered 1 1/8 / 1,5"
HEADSET TYPE	Semi integrated ZS44 / ZS56
MAXIMUM TYRE WIDTH (ETRTO)	56mm
DISC BRAKE STANDARD	International Standard
REAR ROTOR MAX SIZE	185mm
SEATPOST / SEAT CLAMP DIAMETER	31,6mm / 34,9mm
MINIMUM SEATPOST INSERT:	12 cm
BOTTOM BRACKET TYPE	68mm BSA
ISCG	No
FRONT DERAILLEUR TYPE	High direct mount, bottom pull
REAR HUB COMPATIBILITY	135x10mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	292 mm	295 mm
REAR	293 mm	293 mm