

2017

COMMENCAL FCB 29 BLACK 2017



SPECS

FRAME	2017 FCB 700c Disc, Alloy 6061 smooth welded, Integrated routing
SHOCK	-
FORK	2017 FCB 700c, Disc mount
HEADSET	RIDE ALPHA, Campy style
STEM	RIDE ALPHA, Aluminium 2014, 70mm, 31,8mm, 0° Angle
BAR	RIDE ALPHA, 640mm, 20mm rise, aluminium 6061
GRIPS	COMMENCAL, soft compound, Ø32mm
BRAKES	SRAM LEVEL, 160mm / 160mm
SHIFTERS	SRAM APEX 1, 1x11 speed
FRONT / REAR MECH	- / SRAM APEX 1, 1x11 speed, Long Cage
BOTTOM BRACKET	SRAM GXP XR
CRANKSET	SRAM APEX 1, 40t
CHAIN	SRAM PC 1110
CASSETTE	SRAM PG 1030, 11-42T, 11 speed
RIMS	Double Wall, Asymetric profile, 24 holes
HUBS	NOVATEC, 24 holes
SPOKES	PILLAR Spokes, Stainless steel, 1.8mm black, Nylock
TIRES	MAXXIS MUD WRESTLER, 700x33C
SEATPOST	RIDE ALPHA, Ø27,2mm, alloy, no offset, 350mm
SADDLE	RIDE ALPHA, Super light foam, Cromo rails
WEIGHT	9,58 kg
PEDALS INCLUDED	No

TECH

BICYCLE TYPE	Road-Urban hardtail bike
FRAMLE MATERIAL	NEC + ULTRA SL (Aluminium 6061) Triple Butted
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK SPACER DIMENSION	-
RECOMMENDED / MAX FORK HEIGHT	450mm
HEADSET DIMENSION	1"1/8
HEADSET TYPE	Integrated headset type Campa 45° / 45°
MAXIMUM TYRE WIDTH (ETRTO)	28mm
DISC BRAKE STANDARD	DBS International
REAR ROTOR MAX SIZE	160mm
SEATPOST / SEAT CLAMP DIAMETER	27,2mm / 30,6 mm
BOTTOM BRACKET TYPE	68mm BSA
ISCG	Not compatible
FRONT DERAILLEUR	Up swing 34,9mm - down pull
REAR HUB COMPATIBILITY	130x10mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	282 mm	284 mm
REAR	284 mm	282 mm