

2017

COMMENCAL META HT AM RACE 650B BLACK 2017



SPECS

FRAME	2017 Meta HT AM FRAME 650B, alloy 6061 triple butted
SHOCK	∅
FORK	ROCKSHOX LYRIK RC, 160 mm, solo air, 15 mm stealth axle, tapered steerer
HEADSET	RIDE ALPHA ZS44/ZS56
STEM	RIDE ALPHA, Alloy 2014 Forged, 50 mm, 0° Angle, ø 31,8 mm
BAR	RIDE ALPHA, Alloy 7075, double butted, 30 mm rise, 780 mm, ø 31,8 mm
GRIPS	RIDE ALPHA, soft compound, single clamp
BRAKES	AVID DB3, 200mm / 180mm, with matchmaker
SHIFTERS	SRAM NX 1 x 11 speed
FRONT / REAR MECH	∅ / SRAM NX 11 speed, long cage
BOTTOM BRACKET	SRAM GXP XR
CRANKSET	SRAM NX X-Sync, 32 T, 170 mm on S/M and 175 mm on L/XL
CHAIN	SRAM PC 1110
CASSETTE	SRAM PG 1130, 11∅42 T, 11 speed
RIMS	WTB STP i25, 32 holes, double wall, tubeless ready, 25 mm inner
HUBS	FORMULA, 32 holes, sealed bearings
SPOKES / NIPPLES	PILLAR Spokes, Stainless Steel, 2mm, Black, Nylock
TYRES	MAXXIS HR11 27,5" x 2,4" EXO Tubeless Ready
SEATPOST	RIDE ALPHA, ø 31,6 mm, no offset, 400 mm
SADDLE	RIDE ALPHA, CrMo black rails
WEIGHT	13,06 kg
PEDALS INCLUDED	No
ACCESSORIES	Chainstay protector

TECH

BICYCLE TYPE	All mountain Hardtail
FRAME MATERIAL	Aluminium 6061Triple Butted
SHOCK TRAVEL	∅
SHOCK LENGTH / STROKE	∅
PIGGY BACK SHOCK COMPATIBLE	∅
SHOCK BUSHINGS	∅
RECOMMENDED / MAX FORK HEIGHT	530 mm / 544 mm
HEADSET DIMENSION	Tapered 1 1/8" / 1 1/2"
HEADSET TYPE	Semi-integrated ZS44/ZS56
MAXIMUM TYRE WIDTH (ETRTO)	60 mm
DISC BRAKE STANDARD	International Standard
REAR ROTOR MAX SIZE	185 mm
SEATPOST / SEAT CLAMP DIAMETER	31,6 mm / 34,9 mm
MINIMUM SEATPOST INSERT	120 mm
BOTTOM BRACKET TYPE	68 mm BSA
ISCG	No
FRONT DERAILLEUR TYPE	High Direct Mount
REAR HUB COMPATIBILITY	135 x 10 mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	272 mm	273 mm
REAR	274 mm	272 mm