2019

COMMENCAL ABSOLUT 2019

PARTS

A QUESTION?

• (+376) 73 74 93 from Monday to Friday - 9am to 7pm

• customerservice@commencal.com

https://tech.commencal.com/tech/index.php?fiche=337&lang=UK

SPECS

FRAME 2019 ABSOLUT Al V3 Frame, stealth cable routing
FRAME WEIGHT 1.9 kg
SHOCK -

FORK MANITOU Circus Expert, 100 mm, 20 mm axle, tapered
HEADSET RIDE ALPHA ZS44 / ZS56

STEM RIDE ALPHA, 50 mm, 31.8 mm, 0� Angle
BAR RIDE ALPHA, 6061 Alloy series, 760 mm, 30 mm rise
GRIPS RIDE ALPHA, DH Grips, ultra soft compound, single clamp
BRAKES TEKTRO HD - M 285, Hydraulic disc rear brake 160 mm, with reach adjustment
SHIFTERS -
FRONT / REAR MECH - / -
BOTTOM BRACKET BSA STANDARD, threaded
CRANKSET COMMENCAL, 2 pc design, Cr-Mo, 28t, 170 mm
CHAIN YABAN, single speed
CASSETTE 13t sprocket
RIMS ALEXRIMS FR 30, 32 holes
HUBS FORMULA, 32 holes front / NOVATEC, 32 holes rear
SPOKES / NIPPLES SAPIM LEADER spokes, stainless steel, 2.0 mm
TYRES MAXXIS DTH, 26 x 2.3, 60 tpi, skinwall
SEATPOST RIDE ALPHA DJ, alloy 31.6 mm, 300 mm
SADDLE COMMENCAL DJ by Velo, soft padding
WEIGHT 11.3 kg
PEDALS INCLUDED Yes
ACCESSORIES -

TECH

BICYCLE TYPE DIRT semi-rigid
FRAME MATERIAL Aluminium Nuts Triple Butted
FRAME WEIGHT 1.9 kg
SHOCK TRAVEL -
SHOCK LENGTH / STROKE -
PIGGY BACK SHOCK COMPATIBLE -
SHOCK BUSHINGS -
RECOMMENDED / MAX FORK HEIGHT 470 mm / 490 mm
HEADSET DIMENSION Tapered 1-1/8" / 1-1/2"
HEADSET TYPE Semi-integrated ZS44 / ZS56
MAXIMUM TYRE DIMENSION (ETRTO) 57 mm
DISC BRAKE STANDARD Postmount 160 mm
REAR ROTOR MAX SIZE 160 mm
SEATPOST / SEAT CLAMP DIAMETER 31.6 mm / 34.9 mm
BOTTOM BRACKET TYPE 73 mm BSA
ISCG No
FRONT DERAILLEUR TYPE No
REAR HUB COMPATIBILITY 135 x 10 mm

SPOKE LENGTH

WHEEL NON DRIVE SIDE / LEFT DRIVE SIDE / RIGHT
FRONT 258 mm 261 mm
REAR 260 mm 260 mm

Headset

ZS44 / 28,6 - ZS56 / 40

Bottom Bracket

BSA 73mm

Rear hanger

ABSOLUT AL

FreeHub Body

NOVATEC D256SBT

-

BIKES STEP BY STEP