

2019

COMMENCAL FCB 2019



SPECS

FRAME	2019 FCB 700c Disc, Alloy 6061 smooth welded, Integrated routing
SHOCK	-
FORK	2019 FCB 700c, Disc mount
HEADSET	RIDE ALPHA, Campy style
STEM	RIDE ALPHA, Aluminium 2014, 50 mm, 31.8 mm, 0° Angle
BAR	RIDE ALPHA, 640 mm, 20 mm rise, aluminium 6061
GRIPS	RIDE ALPHA, ergonomic grips, plastic one lock, super soft compound
BRAKES	TEKTRO HD-M 285, Hydraulic disc brake 160 mm / 160 mm, with reach adjustment
SHIFTERS	SRAM APEX 1 1 x 11sp
FRONT / REAR MECH	- / SRAM APEX 1 1 x 11sp, longue cage
BOTTOM BRACKET	SRAM GXP XR
CRANKSET	SRAM APEX 1, 40t
CHAIN	KMC X11 - EL BPBP, extra light weight, black tech
CASSETTE	SRAM PG 1130, 11 - 42, 11sp
RIMS	ALEXRIMS DOUBLE WALL, Asymetric profile, 32 holes
HUBS	FORMULA, 32 holes
SPOKES / NIPPLES	SAPIM LEADER spokes, stainless steel, 1.8 mm
TYRES	WTB EXPOSURE, 700 x 32c, skinwall, front & rear
SEATPOST	RIDE ALPHA, 27.2 mm, no offset, 350 mm
SADDLE	RIDE ALPHA, Super light foam, Cr-Mo rails
WEIGHT	9.7 kg
PEDALS INCLUDED	No
ACCESSORIES	-

TECH

BICYCLE TYPE	Road-Urban hardtail bike
FRAME MATERIAL	NEC + ULTRA SL (Aluminium 6061) Triple Butted
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK BUSHINGS	-
RECOMMENDED / MAX FORK HEIGHT	450 mm
HEADSET DIMENSION	1 1/8"
HEADSET TYPE	Integrated headset type Campa 45° / 45°
MAXIMUM TYRE DIMENSION (ETRTO)	34 mm
DISC BRAKE STANDARD	DBS International
REAR ROTOR MAX SIZE	160 mm
SEATPOST / SEAT CLAMP DIAMETER	27.2 mm / 30.6 mm
BOTTOM BRACKET TYPE	68 mm BSA
ISCG	No
FRONT DERAILEUR TYPE	Up swing 34.9 mm - down pull
REAR HUB COMPATIBILITY	130 x 10 mm

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	284 mm	288 mm
REAR	286 mm	284 mm