

2019

COMMENCAL META HT AM ESSENTIAL 2019



SPECS

FRAME	2019 META HT AM, internal cable routing, 27.5
SHOCK	-
FORK	ROCKSHOX YARI RC, 160 mm, 15 mm axle, re- bound, boost. Bottomless Tokens: 2
HEADSET	ACROS Fiber ZS44/ZS56, sealed bearings
STEM	RIDE ALPHA FREERIDE, 40 mm, 31.8 mm, 0 angle
BAR	RIDE ALPHA, Alloy 7075, 780 mm, 31.8 mm, 30 mm rise
GRIPS	RIDE ALPHA, DH Grips, ultra soft compound, single clamp
BRAKES	SRAM LEVEL, 200 mm / 180 mm
SHIFTERS	SRAM NX, 1 x 11 sp
FRONT / REAR MECH	- / SRAM NX, 1 x 11 sp
BOTTOM BRACKET	SRAM Power Spline
CRANKSET	SRAM NX, 32 t, 170 mm on S/M, 175 mm on L/XL
CHAIN	SRAM PC-1110
CASSETTE	SRAM PG-1130, 11-42, 11 sp
RIMS	E13 TRS, 32 holes, 35 mm inner width, tubeless ready
HUBS	FORMULA, 32 holes, sealed bearings
SPOKES / NIPPLES	SAPIM LEADER spokes, stainless steel, 2.0 mm
TYRES	VEETIRECO FLOW SNAPP, 27,5 x 2,6, Skinwall, 72 TPI front and rear (No Tubeless Ready)
SEATPOST	RIDE ALPHA, 31.6 mm, no offset, 400 mm
SADDLE	RIDE ALPHA 278 mm, CrMo rails
WEIGHT	13.7 kg
PEDALS INCLUDED	No
ACCESSORIES	Chainstay protector, seatstay protector

TECH

BICYCLE TYPE	All Mountain Hardtail
FRAME MATERIAL	Aluminium 6061Triple Butted
FRAME WEIGHT	2 kg
SHOCK TRAVEL	-
SHOCK LENGTH / STROKE	-
PIGGY BACK SHOCK COMPATIBLE	-
SHOCK BUSHINGS	-
RECOMMENDED / MAX FORK HEIGHT	555 mm / 561 mm
HEADSET DIMENSION	Tapered 1 1/8" / 1 1/2"
HEADSET TYPE	Semi-integrated ZS44 / ZS56
MAXIMUM TYRE DIMENSION (ETRTO)	27.5" - 71-584 29" - 60-622
DISC BRAKE STANDARD	International Standard
REAR ROTOR MAX SIZE	180 mm
SEATPOST / SEAT CLAMP DIAMETER	31.6 mm / 34.9 mm
MINIMUM SEATPOST INSERT	120 mm
BOTTOM BRACKET TYPE	68 mm BSA
MAXIMUM CHAINRING SIZE	34 T
ISCG	No
FRONT DERAILLEUR TYPE	No
REAR HUB COMPATIBILITY	148 x 12 mm maxle standard boost

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	269 mm	271 mm
REAR	271 mm	269 mm