

2021

COMMENCAL MAXMAX POWER



SPECS

- Specs

CADRE2021 Meta HT 27,5 Power
Alloy 6061, triple butted tubes, T4, T6.

MOTEURSHIMANO DU-E7000
250 W, 60 Nm

BATTERIESHIMANO E8014
418 Wh

AFFICHAGESHIMANO SC-E5000
Unified switch & display featuring: Assist mode selection, Battery charge level, Current Speed, Estimated range, Trip distance, Odometer

AMORTISSEUR-

FOURCHEROCKSHOX 35 Silver R, 150 mm travel
27,5, Coil, rebound, Boost (15 x 110 mm), 44 mm offset. Fender compatible

JEU DE DIRECTIONACROS ZS44 / ZS56
Alloy cups, sealed bearings

POTENCERIDE ALPHA Freeride 40
40 mm extension, 31,8 mm

CINTRERIDE ALPHA R15
31,8 mm, 760 mm width, 15 mm rise, Alloy 6061

GRIPSRIDE ALPHA DH
Ultra-soft compound, single clamp, black

FREINSSRAM Guide T, 4 pistons, MatchMaker compatible
Rotors: SRAM G2 CleanSweep 200 mm, 6-bolt

SHIFTERSSHIMANO Deore
10s

GUIDE CHAÎNERIDE ALPHA E8000
34t

DERAILLEURSHIMANO Deore
10s

BOITIER DE PEDALIERSHIMANO

MANIVELLESSHIMANO FC-E8000
165 mm crank arms

PLATEAUSHIMANO SM-CRE70-B
34t

CHAÎNEKMC e10
10s, EPT Anti-rust

CASSETTESHIMANO Deore
10s, 11-46t

JANTESE13 LG1 EN Base
27,5, 32h, 35 mm inner width

MOYEURRear: FORMULA eHL-148S - Front: FORMULA DC-711
Rear: 32h, sealed bearings, e-bike specific - Front: 32h, sealed bearings

RAYONSSAPIM Strong
J-Bend, 2,34 / 2.0 mm, double butted, stainless, with Nylok, black

PNEUSRear: SCHWALBE Johnny Watts - Front: SCHWALBE Johnny Watts
Rear: 27,5 x 2,8, RaceGuard, Addix - Front: 27,5 x 2,8, RaceGuard, Addix

TIGE DE SELLERRIDE ALPHA
31,6 mm, 400 mm on S/M, 450 mm on L/X

SELLEFABRIC Scoop Flat Sport
Steel rails

POIDS20,6 KG
Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.

PEDALESYes

COULEURHeritage Green
Shiny finish

ACCESSOIRESRIDE ALPHA CNC Alloy pedals, chainstay protector, seatstay protector, battery charger, user manual

RECYCLAGE BATTERIE PARTNERSHIP WITH SHIMANO
In partnership with SHIMANO, COMMENCAL supports a voluntary battery recycling program for ebike batteries. For each META POWER sold COMMENCAL will contribute 7EUR to fundraising organisation COREPILE. This sum is paid through SHIMANO France. When your battery reaches the end of its life, it would be great if you could send it back to us for recycling. Contact us for more info on the procedure.
- Vidéos

TECH

- Tech

TYPE DE VELOAll Mountain Hardtail E-bike

CADREAl 6061 T6

POIDS DU CADRE-

DEBATTEMENT ARRIERE-

ENTRE-AXE / COURSE-

COMPATIBLE PIGGY BACK-

BUSELURES AMORTISSEUR-

HAUTEUR DE FOURCHE RECOMMANDEE / MAX551 mm / 561 mm

DOUILLE DE DIRECTIONTapered

JEU DE DIRECTIONSemi-integrated ZS44 / ZS56

LARGEUR MAXIMALE PNEUS (ETRTO)71

STANDARD FREIN A DISQUEInternational standard

DIAMETRE MAX DISQUE DE FREIN AR200 mm

DIAMETRE TIGE DE SELLE / COLLIER DE SELLE31,6 mm / 34,9 mm

INSERTION MINIMUM DE TIGE DE SELLE120 mm

BOITIER DE PEDALIERShimano E-bike interface

ISCGe-Chainguide Shimano

DERAILLEUR AVANTNo

AXE DE ROUE ARRIERE148 x 12 mm standard Maxle
- Géométrie
- Tailles
- News

SPOKE LENGTH

WHEEL	NON DRIVE SIDE / LEFT	DRIVE SIDE / RIGHT
FRONT	268 mm	270 mm
REAR	270 mm	268 mm