

2021

COMMENCAL META HT AM ESSENTIAL 2021



SPECS

- Specs
 - CADRE**2021 Meta HT AM
Alloy 6061, triple butted tubes, T4, T6.
 - AMORTISSEUR-**
 - FOURCHEROCKSHOX** Yari RC, 160 mm travel
27.5", Motion Control damper, Debonair, rebound, Boost (15 x 110 mm), 46 mm offset
 - JEU DE DIRECTION**ACROS ZS44 / ZS56
Alloy cups, sealed bearings
 - POTENCERIDE** ALPHA Freeride 40
40 mm extension, 31,8 mm
 - CINTRERIDE** ALPHA R27
31,8 mm, 780 mm width, 27 mm rise, Alloy 6061
 - GRIPSRIDE** ALPHA DH
Ultra-soft compound, single clamp, black
 - FREIN**SRAM Guide T, 4 pistons, MatchMaker compatible
Rotor: SRAM G2 CleanSweep 200 / 180 mm, 6-bolt
 - SHIFTERS**SRAM SX Eagle
12 sp
 - GUIDE CHAINE-**
 - DERAILLEURS**SRAM SX Eagle
12 sp
 - BOITIER DE PEDALIERS**SRAM DUB
Threaded
 - PEDALIERS**SRAM X1 1000 Eagle, 170 mm crank arms, DUB, Boost
Chainring: SRAM X1 1000 Eagle, 32t, Narrow-Wide
 - CHAINES**SRAM NX
12 sp
 - CASSETTES**SRAM PG-1210
12 sp, 11-50t
 - JANTESSPANK** Oozy 395+
27.5", 32h, 35 mm inner width
 - MOYEUX**Rear: FORMULA DC-348Front: FORMULA DC-711
Rear: 32h, sealed bearings - Front: 32h, sealed bearings
 - RAYONSSAPIM** Leader
J-Bend 2.0 mm, stainless, with Nylok, black
 - PNEUS**Rear: MAXXIS RekonFront: MAXXIS High Roller II
Rear: 27,5 x 2.8, EXO, Tubeless Ready - Front: 27,5 x 2.8, EXO, Tubeless Ready
 - TIGE DE SELLE**KS Rage-I
31,6 mm, travel: 125 mm on S, 150 mm on M, 170 mm on L, 190 mm on XL, SouthPaw alloy remote
 - SELLE**FABRIC Scoop Flat Sport
Steel rails
 - POIDS**13,8 kg
Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.
 - PEDALES**No
 - COULEUR**Heritage Green
Shiny finish
 - ACCESSOIRES**Chainstay protector, seatstay protector

- Vidéos

TECH

- Tech
 - TYPE DE VELO**Hardtail Enduro
 - CADRE**Al 6061 T6
 - POIDS DU CADRE**2,1 kg
 - DEBATTEMENT ARRIERE-**
 - ENTRE-AXE / COURSE-**
 - COMPATIBLE PIGGY BACK-**
 - BUSELURES AMORTISSEUR-**
 - HAUTEUR DE FOURCHE RECOMMANDEE / MAX**552 mm / 562 mm
 - DOUILLE DE DIRECTION**TAPERED 1-1/8" / 1-1/2"
 - JEU DE DIRECTION**ZS44 / ZS56
 - LARGEUR MAXIMALE PNEUS (ETRTO)**27,5" - 71-584 / 29" - 60-622
 - STANDARD FREIN A DISQUE**INTERNATIONAL STANDARD
 - DIAMETRE MAX DISQUE DE FREIN AR**200 mm
 - DIAMETRE TIGE DE SELLE / COLLIER DE SELLE**31,6 mm / 34,9 mm
 - BOITIER DE PEDALIER**BSA 68 mm
 - ISCG**No
 - DERAILLEUR AVANT**No
 - AXE DE ROUE ARRIERE**12 x 148 MAXLE STANDARD BOOST

- Géometrie
- Tailles
-
- News

LONGUEUR DES RAYONS

ROUE	GAUCHE / CÔTÉ SANS TRANSMISSION	DROIT / CÔTÉ TRANSMISSION
AVANT	269 mm	270 mm
ARRIÈRE	270 mm	268 mm

