2021

COMMENCAL META POWER SX RACE

SPECS

•
Specs
CADRE2021 Meta Power SX, 165 mm travel
27.5", Alloy 6066, triple butted tubes, T4, T6. Enduro bearings

MOTEURSHIMANO DU-EP800
250 W, 85 Nm

BATTERIESHIMANO BT-E8036
630Wh

AFFICHAGESHIMANO SC-EM800
LCD colored display featuring: Clock, Assist mode display, Battery charge level, Current Speed, Maximum speed, Average speed, Trip distance, Trip time, Estimated range, Range overview, Cadence, Human output power (as scale indicator), Calorie setting, Maintenance alert, Bluetooth LE connection (for E-Tube Project communication)

AMORTISSEURROCKSHOX SuperDeluxe Coil Ultimate
230 x 65 mm, LSC, rebound, 2-position adjustment. Spring rates: 300 lbs on S, 350 lbs on M, 400 lbs on L, 450 lbs on XL

FOURCHEROCKSHOX Zeb Ultimate E-Bike, 180 mm travel
27.5", Charger 2.1 damper, Debonair, LSC, HSC, rebound, Boost (15 x 110 mm), 38 mm offset

JEU DE DIRECTIONACROS ZS56 / ZS66
Alloy cups, sealed bearings

POTENCERIDE ALPHA Freeride 40
40 mm extension, 31,8 mm

CINTRERIDE ALPHA R20 E-Bike
31,8 mm, 780 mm width, 20 mm rise, Alloy 6061, electric wire internal routing

GRIPSRIDE ALPHA DH
Ultra-soft compound, single clamp, black

FREINSSRAM Code R
4 pistons, MatchMaker compatible

DISQUESSRAM Centerline 220 mm
6-bolt, bolt-on magnet

SHIFTERSSRAM GX Eagle
12s, Single Click

GUIDE CHAINERIDE ALPHA EP8
32-34t

DERAILLEURSRAM GX Eagle
12s

BOITIER DE PEDALIERSHIMANO

MANIVELLESE13 E*Spec EP8
160 MM crank arms

PLATEAUE13 E*Spec Plus EP8
34t, Narrow-Wide, direct mount

CHAINESRAM GX Eagle
12s

CASSETTESRAM GX Eagle
12s, 11-52t

JANTESE13 E*Spec
27.5", 28h/32h, 30 mm inner width

MOYEUXRear: E13 E*Spec - Front: E13 E*Spec
Rear: 32h, sealed bearings, e-bike specific - Front: 28h, sealed bearings

RAYONSE13 E*Spec
J-bend, triple-butted spokes

PNEUSRear: SCHWALBE Big Betty - Front: SCHWALBE Magic Mary
Rear: 27.5 x 2.4, Addix Soft, Super Gravity, Tubeless Ready - Front: 27.5 x 2.4, Addix Soft, Super Gravity, Tubeless Ready

TIGE DE SELLEKINDSHOCK Lev Si
31,6 mm, travel: 125 mm on S, 150 mm on M, 175 mm on L & XL, SouthPaw alloy remote

SELLEFABRIC Scoop Flat Elite
Cr-Mo rails

POIDS24,6 kg
Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.

PEDALESYes

COULEURMatte Graphite
Matte finish

ACCESSOIRESRIDE ALPHA CNC pedals, motor protector, chainstay protector, seatstay protector, user manual
META POWER bikes are delivered with Shimano Europlug (CEE 7/7 norm) battery charger, a plug adapter is necessary for customers living in countries using different standards.

RECYCLAGE BATTERIE Partnership with SHIMANO
In partnership with SHIMANO, COMMENCAL supports a voluntary battery recycling program for ebike batteries. For each META POWER sold COMMENCAL will contribute 7EUR to fundraising organisation COREPILE. This sum is paid through SHIMANO France. When your battery reaches the end of its life, it would be great if you could send it back to us for recycling. Contact us for more info on the procedure.

TECH

•
Tech
TYPE DE VELOE-bike Enduro 27,5"

CADREAL-6061 + AL-6066

POIDS DU CADRE4,1 kg - With plastic accessories.

DEBATTEMENT ARRIERE165 mm

ENTRE-AXE / COURSE230 x 65 mm

COMPATIBLE PIGGY BACK Yes

BUSELURES AMORTISSEUR20 x 10 mm front / 12,7 x 10 mm rear

HAUTEUR DE FOURCHE RECOMMANDEE / MAX583 mm / 593 mm

DOUILLE DE DIRECTION Tapered

JEU DE DIRECTIONZS44 / ZS56

LARGEUR MAXIMALE PNEUS (ETRTO)65 mm - 622

STANDARD FREIN A DISQUE Postmount

DIAMETRE MAX DISQUE DE FREIN AR220 mm

DIAMETRE TIGE DE SELLE / COLLIER DE SELLE31,6 mm / 34,9 mm

BOITIER DE PEDALIERSHIMANO EP800

ISCGYes (SHIMANO Standard)

DERAILLEUR AVANT No

AXE DE ROUE ARRIERE12 x 148 mm, Maxle standard

•
Géometrie
•
Tailles
•
•
News