

2022

COMMENCAL MAXMAX POWER



SPECS

CADRE

MAXMAX POWER

27.5", Alloy 6061, triple butted tubes, T4, T6.

MOTEUR

SHIMANO DU-E7000

Max. torque: 60N.m, 250W

BATTERIE

SHIMANO BT-E8035

504Wh internal battery

AFFICHAGE

SHIMANO SC-E5000

Unified switch & display featuring: Assist mode selection, Battery charge level, Current Speed, Estimated range, Trip distance, Odometer

AMORTISSEUR

-

FOURCHE

ROCKSHOX 35 Silver R, 150 mm travel

27.5", Coil, rebound, Boost (15 x 110 mm), 44 mm offset

JEU DE DIRECTION

ACROS ZS44 / ZS56

Alloy cups, sealed bearings

POTENCE

RIDE ALPHA Freeride 40

40 mm extension, 31,8 mm

CINTRE

RIDE ALPHA R20 POWER on S - RIDE ALPHA R27 POWER on M / L / XL

Internal DI2 cable routing - 31.8 mm, 760 mm width, 20 mm rise, Alloy 6061 on S - 31.8 mm, 780 mm width, 27 mm rise, Alloy 6061 on M / L - 31.8 mm, 800 mm width, 27 mm rise, Alloy 6061 on XL

GRIPS

RIDE ALPHA DH

Ultra-soft compound, single clamp, black

FREINS

SRAM Guide T, 4 pistons, MatchMaker compatible

Rotors: SRAM G2 CleanSweep 200 mm, 6-bolt

SHIFTERS

SHIMANO Deore, Linkglide

10s

GUIDE CHAINE

RIDE ALPHA E8000

34t

DERAILLEUR

SHIMANO Deore, Linkglide

10s

BOITIER DE PEDALIER

SHIMANO

MANIVELLES

SHIMANO FC-E8000

165 mm crank arms

PLATEAU

SHIMANO SM-CRE70-B

34t

CHAINE

SHIMANO Linkglide 10/11s

10/11s

CASSETTE

SHIMANO Deore, Linkglide

10s, 11-43

JANTES

E13 LG1 EN Base

27.5, 32h, 35 mm inner width

MOYEURS

Rear: FORMULA eHL-148S - Front: FORMULA DC-711

Rear: 32h, sealed bearings, e-bike specific - Front: 32h, sealed bearings

RAYONS

SAPIM Strong

J-Bend, 2.34 / 2.0 mm, double butted, stainless, with Nylok, black

PNEUS

Rear: SCHWALBE Johnny Watts - Front: SCHWALBE Johnny Watts

Rear: 27.5 x 2.8, RaceGuard, Addix - Front: 27.5 x 2.8, RaceGuard, Addix

TIGE DE SELLE

RIDE ALPHA

31,6 mm, 400 mm on S/M, 450 mm on L/X

SELLE

FIZIK Terra Aidon X5

S-Alloy Mobius rails

POIDS

20,6 KG

Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.

PEDALES

Yes

COULEUR

Dark Slate

Matte Finish

ACCESSOIRES

RIDE ALPHA CNC pedals, chainstay protector, seatstay protector, battery charger

Battery charger: SHIMANO EC-E6002, Compact size & lightweight

RECYCLAGE BATTERIE

PARTNERSHIP WITH SHIMANO

In partnership with SHIMANO, COMMENCAL supports a voluntary battery recycling program for ebike batteries. For each META POWER sold COMMENCAL will contribute 7EUR to fundraising organisation COREPILE. This sum is paid through SHIMANO France. When your battery reaches the end of its life, it would be great if you could send it back to us for recycling. Contact us for more info on the procedure.

TECH

TYPE DE VELO

HARDTRAIL E-BIKE

CADRE

Al 6061 T6

POIDS DU CADRE

-

DEBATTEMENT ARRIERE

-

ENTRE-AXE / COURSE

-

COMPATIBLE PIGGY BACK

-

BUSELURES AMORTISSEUR

-

HAUTEUR DE FOURCHE RECOMMANDEE / MAX

551 mm / 561 mm

DOUILLE DE DIRECTION

tapered

JEU DE DIRECTION

ZS44 / ZS56

LARGEUR MAXIMALE PNEUS (ETRTO)

71 mm

STANDARD FREIN A DISQUE

International standard

DIAMETRE MAX DISQUE DE FREIN AR

200 mm

DIAMETRE TIGE DE SELLE / COLLIER DE SELLE

31,6 mm / 34,9 mm

INSERTION MINIMUM DE TIGE DE SELLE

120 mm

BOITIER DE PEDALIER

Shimano E-bike interface

ISCG

e-Chainguide Shimano

DERAILLEUR AVANT

No

AXE DE ROUE ARRIERE

148 x 12 mm std Maxle

GEOMETRIE

Tailles