

2022

COMMENCAL META HT AM OHLINS 2022



SPECS

CADRE

2022 Meta HT AM - 29"/27" on S / M & 29"/29" on L / XL

Alloy 6061, triple butted tubes, T4, T6.

AMORTISSEUR

-

FOURCHE

OHLINS RXF36 m.2 Air, 150 mm travel

29", TTX 18 damper, Ramp Up chamber, LSC, HSC, rebound, Boost (15 x 110 mm), 44 mm offset

JEU DE DIRECTION

ACROS ZS44 / ZS56

Alloy cups, sealed bearings

POTENCE

RIDE ALPHA Freeride 40

40 mm extension, 31,8 mm

CINTRE

RIDE ALPHA R20 on S - RIDE ALPHA R27 on M / L / XL

31.8 mm, 760 mm width, 20 mm rise, Alloy 6061 on S - 31.8 mm, 780 mm width, 27 mm rise, Alloy 6061 on M / L - 31.8 mm, 800 mm width, 27 mm rise, Alloy 6061 on XL

GRIPS

ODI Elite Motion

Soft pro compound, single clamp, black

FREINS

SHIMANO XT, 4 pistons, I-Spec EV compatible

Rotor: GALFER Disc Wave 203 mm, 6-bolt

SHIFTERS

SRAM GX Eagle

12s

GUIDE CHAINE

-

DERAILLEUR

SRAM GX Eagle

12s

BOITIER DE PEDALIER

SRAM BSA

Threaded

PEDALIER

SRAM GX Eagle, 170 mm crank arms, DUB, Boost

Chainingrg: SRAM GX Eagle, 32t, Narrow-Wide

CHAINE

SRAM GX Eagle

12s

CASSETTE

SRAM GX Eagle

12s, 10-52t

JANTES

SPANK Spike Race 33

REAR: 27.5", 32h, 28 mm inner width on S / M29", 32h, 28 mm inner width rear on L / XL - FRONT: 29", 32h, 28 mm inner width on S / M / L / XL

MOYEUX

Rear: FORMULA MSL-148AFront: FORMULA DC-711

Rear: 32h, sealed bearings - Front: 32h, sealed bearings

RAYONS

SAPIM Race

J-Bend, 2.0-1.8-2.0mm, double butted, stainless, with Nylok, black

PNEUS

Rear: MAXXIS Dissector - Front: MAXXIS Dissector

REAR: 27.5" x 2.6", 3C MaxxTerra, New EXO+, Tubeless Ready on S / M - 29" x 2.6", 3C MaxxTerra, New EXO+, Tubeless Ready on L / XL - FRONT: 29" x 2.6", 3C MaxxTerra, New EXO+, Tubeless Ready on S / M / L / XL

TIGE DE SELLE

SDG Tellis

31.6 mm, travel: 125 mm on S, 150 mm on M, 170 mm on L, 200 mm on XL

SELLE

SDG Bel Air V3 Atmos

Lux-Alloy Rails

POIDS

13.5 kg

Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.

PEDALES

No

COULEUR

Silver

Matte Finish

ACCESSOIRES

Chainsstay protector, seatstay protector

- Vidéos

TECH

TYPE DE VELO

Hardtail Enduro

CADRE

Al 6061 T6

POIDS DU CADRE

-

DEBATTEMENT ARRIERE

-

ENTRE-AXE / COURSE

-

COMPATIBLE PIGGY BACK

-

BUSELURES AMORTISSEUR

-

HAUTEUR DE FOURCHE RECOMMANDEE / MAX

561 MM / 571 MM

DOUILLE DE DIRECTION

TAPERED 1-1/8" / 1-1/2"

JEU DE DIRECTION

ZS44 / ZS56

LARGEUR MAXIMALE PNEUS (ETRTO)

27.5" - 71-584

STANDARD FREIN A DISQUE

INTERNATIONAL STANDARD

DIAMETRE MAX DISQUE DE FREIN AR

200 MM

DIAMETRE TIGE DE SELLE / COLLIER DE SELLE

31,6 MM / 34,9 MM

BOITIER DE PEDALIER

BSA 68 MM

ISCG

-

DERAILLEUR AVANT

-

AXE DE ROUE ARRIERE

148 x 12 STANDARD MAXLE

- Géométrie
- Tailles