

2022

COMMENCAL META HT AM RIDE 2022



SPECS

CADRE

2022 Meta HT AM - 29"/27" on S / M & 29"/29" on L / XL

Alloy 6061, triple butted tubes, T4, T6.

AMORTISSEUR

-

FOURCHE

ROCKSHOX 35 Gold RL, 150 mm travel

29", DebonAir, rebound, Boost (15 x 110 mm), 44 mm offset, 0 Token

JEU DE DIRECTION

ACROS ZS44 / ZS56

Alloy cups, sealed bearings

POTENCE

RIDE ALPHA Freeride 40

40 mm extension, 31,8 mm

CINTRE

RIDE ALPHA R20 on S - RIDE ALPHA R27 on M / L / XL

31.8 mm, 760 mm width, 20 mm rise, Alloy 6061 on S - 31.8 mm, 780 mm width, 27 mm rise, Alloy 6061 on M / L - 31.8 mm, 800 mm width, 27 mm rise, Alloy 6061 on XL

GRIPS

ODI Elite Motion

Soft pro compound, single clamp, black

FREINS

SRAM Level, 2 pistons, Hydraulic disc brake

Rotor: SRAM G2 CleanSweep 200 / 180 mm, 6-bolt

SHIFTERS

SRAM SX Eagle

12s

GUIDE CHAINE

-

DERAILLEUR

SRAM SX Eagle

12s

BOITIER DE PEDALIER

SRAM BSA

Threaded

PEDALIER

SRAM X1 1000 Eagle, 170 mm crank arms, DUB, Boost

Chaining: SRAM X1 1000 Eagle, 32t, Narrow-Wide

CHAINE

SRAM NX Eagle

12s

CASSETTE

SRAM PG-1210

12s, 11-50t

JANTES

E13 LG1 EN Base

REAR: 27.5", 32h, 30 mm inner width on S / M - 29", 32h, 30 mm inner width rear on L / XL - FRONT: 29", 32h, 30 mm inner width on S / M / L / XL

MOYEUR

Rear: FORMULA DC-348A Front: FORMULA DC-711

Rear: 32h, sealed bearings - Front: 32h, sealed bearings

RAYONS

SAPIM Leader

J-Bend 2.0 mm, stainless, with Nyllok, black

PNEUS

Rear: MAXXIS Dissector - Front: MAXXIS Dissector

REAR: 27.5" x 2.6", EXO, Tubeless Ready on S / M - 29" x 2.6", EXO, Tubeless Ready, on L / XL - FRONT: 29" x 2.6" WT, EXO, Tubeless Ready on S / M / L / XL

TIGE DE SELLE

RIDE ALPHA

31,6 mm, 400 mm on S/M, 450 mm on L/X

SELLE

SDG Bel Air V3

Steel rails

POIDS

14,2 kg

Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.

PEDALES

No

COULEUR

Dirt

Shiny Finish

ACCESSOIRES

Chainstay protector, seatstay protector

- Vidéos

TECH

TYPE DE VELO

Hardtail Enduro

CADRE

Al 6061 T6

POIDS DU CADRE

-

DEBATTEMENT ARRIERE

-

ENTRE-AXE / COURSE

-

COMPATIBLE PIGGY BACK

-

BUSELURES AMORTISSEUR

-

HAUTEUR DE FOURCHE RECOMMANDEE / MAX

561 MM / 571 MM

DOUILLE DE DIRECTION

TAPERED 1-1/8" / 1-1/2"

JEU DE DIRECTION

ZS44 / ZS56

LARGEUR MAXIMALE PNEUS (ETRTO)

27.5" - 71-584

STANDARD FREIN A DISQUE

INTERNATIONAL STANDARD

DIAMETRE MAX DISQUE DE FREIN AR

200 MM

DIAMETRE TIGE DE SELLE / COLLIER DE SELLE

31,6 MM / 34,9 MM

BOITIER DE PEDALIER

BSA 68 MM

ISCG

-

DERAILLEUR AVANT

-

AXE DE ROUE ARRIERE

148 x 12 STANDARD MAXLE

- Géometrie
- Tailles