

2023

COMMENCAL META POWER SX BOSCH ESSENTIAL 70'S GREEN



SPECS

CADRE META POWER BOSCH, 165 mm travel 29"-27.5", Alloy 6066, triple butted tubes, T4, T6. Bolu bearings
MOTEUR BOSCH Performance Line CX Max. torque: 85N.m, 250W
BATTERIE BOSCH PowerTube 625 625Wh
BATTERY CHARGER BOSCH 4A Charger Compact size & lightweight
AFFICHAGE BOSCH System Controller
SWITCH BOSCH Mini Remote
AMORTISSEUR FOX Float X Performance 230 x 65 mm, LSR, 2-position adjustment
FOURCHE FOX 38 Performance E-Bike, 170 mm travel 29", Fit Grip damper, 3 positions, rebound, Boost (15 x 110 mm), 44 mm offset, oversized crown, 3 Tokens
JEU DE DIRECTION ACROS Z556 / Z566 Alloy cups, sealed bearings
POTENCE RIDE ALPHA 40 EXTERNAL 40 mm extension, 31,8 mm
CINTRE RIDE ALPHA R20 POWER on S - RIDE ALPHA R27 POWER on M / L / XL Internal Di2 cable routing - 31.8 mm, 760 mm width, 20 mm rise, Alloy 6061 on S - 31.8 mm, 780 mm width, 27 mm rise, Alloy 6061 on M / L - 31.8 mm, 800 mm width, 27 mm rise, Alloy 6061 on XL
GRIPS ODI Longneck Soft pro compound, single clamp, black
FREINS SHIMANO SLX 4 pistons, I-Spec EV compatible
DISQUES SHIMANO SM-RT66 220 mm 6-bolt
SHIFTERS SHIMANO SLX 12s, RapidFire Plus
GUIDE CHAÎNE RIDE ALPHA Upper Guide 32-34t
DERAILLEUR SHIMANO SLX 12s
BOÎTIER DE PEDALIER BOSCH
MANIVELLES E13 E*Spec Plus BOSCH CX 160 mm crank arms
PLATEAU E13 E*Spec Plus BOSCH CX 34t, direct mount
CHAÎNE SHIMANO SLX 12s
CASSETTE SHIMANO SLX 12s, 10-51t
JANTES Rear: DT SWISS H1900 Spline - Front: DT SWISS H1900 Spline Rear: 27.5", 28h, sleeved, 30 mm inner width - Front: 29", 28h, sleeved, 30 mm inner width
MOYEURS Rear: DT SWISS 370 - Front: DT SWISS 370 Rear: 28h, sealed bearings, 18t, e-bike specific - Front: 28h, sealed bearings
RAYONS DT SWISS Hybrid 1 Straightpull, 2.34/2.0mm, double butted, stainless, with Nylok, black
PNEUS Rear: MAXXIS DHR II - Front: MAXXIS Assegai Rear: 27.5" x 2.4" WT, 3C MaxxTerra, DD, TR - Front: 29" x 2.5" WT, 3C MaxxGrip, Exo+, TR
TIGE DE SELLE KS Rage I 31.6 mm, travel: 125 mm on S, 170 mm on M/L, 190 mm on XL, SouthPaw alloy remote
SELLE FIZIK Terra Aidon X5 145 mm width, S-Alloy Mobius rails
POIDS - kg Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.
PÉDALES Yes
COULEUR 70'S Green Shiny Finish
ACCESSOIRES RIDE ALPHA CNC pedals, fork fender, motor protector, chainstay protector, seatstay protector, user manual *Les spécifications du vélo sont susceptibles d'être modifiées sans préavis.

RECYCLAGE BATTERIE
Partnership with BOSCH

The battery (used up, damaged, defective) must be recycled. Each national distributor is responsible for providing the dealer with a free recycling solution. Applicable laws: Battery Act, Directive 2006/66/EC, BattG in Germany too. Robert Bosch GmbH recommends concluding a contract with a national service provider for returning batteries in each case.

TECH

TYPE DE VELO E-BIKE ENDURO 29"/27"
CADRE AL-6061 + AL-6066
POIDS DU CADRE - kg - With plastic accessories.
DEBATTEMENT ARRIERE 165 mm
ENTRE-AXE / COURSE 230 x 65 mm
COMPATIBLE PIGGY BACK Yes
BUSELURES AMORTISSEUR 20 x 10 mm front
HAUTEUR DE FOURCHE RECOMMANDEE / MAX 563 mm / 593 mm
DOUILLE DE DIRECTION Tapered
JEU DE DIRECTION Z556 / Z566
LARGEUR MAXIMALE PNEUS (ETRTO) 65 - 584 mm
STANDARD FREIN A DISQUE PM160
DIAMETRE MAX DISQUE DE FREIN AR 220 mm
DIAMETRE TIGE DE SELLE / COLLIER DE SELLE 31.6 mm / 34.9 mm
BOÎTIER DE PEDALIER BOSCH E-BIKE
ISCG Yes (BOSCH Standard)
DERAILLEUR AVANT No
AXE DE ROUE ARRIERE 12 x 148 mm

- Géométrie
- Tailles