2023

COMMENCAL META POWER SX BOSCH RIDE METALLIC GREEN

SPECS

CADRE
META POWER BOSCH, 165 mm travel

29'-27.5", Alloy 6066, triple butted tubes, T4, T6. Bolu bearings

MOTEUR
BOSCH Performance Line CX

Max. torque: 85N.m, 250W

BATTERIE
BOSCH PowerTube 625

625Wh

BATTERY CHARGER
BOSCH 4A Charger

Compact size & lightweight

AFFICHAGE
BOSCH System Controller

SWITCH
BOSCH Mini Remote

AMORTISSEUR
ROCKSHOX Deluxe Select R

230 x 65 mm, rebound, DebonAir

FOURCHE
ROCKSHOX Domain RC, 170 mm travel

29", Motion Control damper, rebound, LSC, DebonAir, Boost (15 x 110 mm), 44 mm offset, 1 Token

JEU DE DIRECTION
ACROS ZS56 / ZS66

Alloy cups, sealed bearings

POTENCE
RIDE ALPHA 40 EXTERNAL

40 mm extension, 31,8 mm

CINTRE
RIDE ALPHA R20 POWER on S - RIDE ALPHA R27 POWER on M / L / XL

Internal Di2 cable routing - 31.8 mm, 760 mm width, 20 mm rise, Alloy 6061 on S - 31.8 mm, 780 mm width, 27 mm rise, Alloy 6061 on M / L - 31.8 mm, 800 mm width, 27 mm rise, Alloy 6061 on XL

GRIPS
ODI Elite Motion

Soft pro compound, single clamp, black

FREINS
SRAM Guide RE

4 pistons

DISQUES
SRAM HS2 220 mm

6-bolt

SHIFTERS
SRAM SX Eagle

12s

GUIDE CHAINE
RIDE ALPHA Upper Guide

32-34t

DERAILLEUR
SRAM SX Eagle

12s

BOITIER DE PEDALIER
BOSCH

MANIVELLES
E13 E*Spec Plus BOSCH CX

160 mm crank arms

PLATEAU
E13 E*Spec Plus BOSCH CX

34t, direct mount

CHAINE
SRAM NX Eagle

12s

CASSETTE
SRAM PG-1210

12s, 11-50t

JANTES
Rear: SPANK Spike Race 33 - Front: SPANK Spike Race 33

Rear: 27.5", 32h, 28 mm inner width rear - Front: 29", 32h, 28 mm inner width front

MOYEUX
Rear: FORMULA eHL-148S - Front: FORMULA DC-711

Rear: 32h, sealed bearings, e-bike specific - Front: 32h, sealed bearings

RAYONS
SAPIM Strong

J-Bend, 2.34/2.0mm, double butted, stainless, with Nylok, black

PNEUS
Rear: MAXXIS DHR II - Front: MAXXIS Assegai

Rear: 27.5" x 2.4" WT, 3C Maxx Terra, Double Down, 3C, TR - Front: 29" x 2.5" WT, 3C Maxx Grip, Exo+, TR

TIGE DE SELLE
KS Rage I

31.6 mm, travel: 125 mm on S, 170 mm on M/L, 190 mm on XL, SouthPaw alloy remote

SELLE
FIZIK Terra Aidon X5

145 mm width, S-Alloy Mobius rails

POIDS
- kg

Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.

PEDALES
Yes

COULEUR
Metallic Green

Matte Finish

ACCESSOIRES
RIDE ALPHA CNC pedals, fork fender, motor protector, chainstay protector, seatstay protector, user manual

*Les spécifications du vélo sont susceptibles d'être modifiées sans préavis.

RECYCLAGE BATTERIE
Partnership with BOSCH

The battery (used up, damaged, defective) must be recycled. Each national distributor is responsible for providing the dealer with a free recycling solution.Applicable laws: Battery Act, Directive 2006/66/EC, BattG in Germany too.Robert Bosch GmbH recommends concluding a contract with a national service provider for returning batteries in each case.

TECH

TYPE DE VELO
E-BIKE ENDURO 29"/27"

CADRE
AL-6061 + AL-6066

POIDS DU CADRE
- kg - With plastic accessories.

DEBATTEMENT ARRIERE
165 mm

ENTRE-AXE / COURSE
230 x 65 mm

COMPATIBLE PIGGY BACK
Yes

BUSELURES AMORTISSEUR
20 x 10 mm front

HAUTEUR DE FOURCHE RECOMMANDEE / MAX
583 mm / 593 mm

DOUILLE DE DIRECTION
Tapered

JEU DE DIRECTION
ZS56 / ZS66

LARGEUR MAXIMALE PNEUS (ETRTO)
65 - 584 mm

STANDARD FREIN A DISQUE
PM160

DIAMETRE MAX DISQUE DE FREIN AR
220 mm

DIAMETRE TIGE DE SELLE / COLLIER DE SELLE
31,6 mm / 34,9 mm

BOITIER DE PEDALIER
BOSCH E-BIKE

ISCG
Yes (BOSCH Standard)

AXE DE ROUE ARRIERE
12 x 148 mm

- Géometrie
- Tailles