

2023

COMMENCAL META POWER SX BOSCH SIGNATURE LILAC



SPECS

CADRE

META POWER BOSCH, 165 mm travel

29"-27.5", Alloy 6066, triple butted tubes, T4, T6, Bolu bearings

MOTEUR

BOSCH Performance Line CX

Max. torque: 85N.m, 250W

BATTERIE

BOSCH PowerTube 625

625Wh

BATTERY CHARGER

BOSCH 4A Charger

Compact size & lightweight

AFFICHAGE

BOSCH System Controller

SWITCH

BOSCH Mini Remote

AMORTISSEUR

FOX Float X Factory

230 x 65 mm, HSC, LSC, HSR,LSR, 2-position adjustment

FOURCHE

FOX 38 Factory E-Bike, 170 mm travel

29", Grip2 damper, HSR, LSR, HSC, LSC, Boost (15 x 110 mm), 44 mm offset, oversized crown, 3 Tokens

JEU DE DIRECTION

ACROS ZS56 / ZS66

Alloy cups, sealed bearings

POTENCE

RIDE ALPHA 40 EXTERNAL

40 mm extension, 31,8 mm

CINTRE

RIDE ALPHA R20 POWER on S - RIDE ALPHA R27 POWER on M / L / XL

Internal Di2 cable routing - 31.8 mm, 760 mm width, 20 mm rise, Alloy 6061 on S - 31.8 mm, 780 mm width, 27 mm rise, Alloy 6061 on M / L - 31.8 mm, 800 mm width, 27 mm rise, Alloy 6061 on XL

GRIPS

ODI Elite Motion

Soft pro compound, single clamp, black

FREINS

SHIMANO XT

4 pistons, I-Spec EV compatible

DISQUES

SHIMANO SM-RT66 220 mm

6-bolt

SHIFTERS

SHIMANO XT

12s

GUIDE CHAINE

RIDE ALPHA Upper Guide

32-34t

DERAILLEUR

SHIMANO XT

12s

BOITIER DE PEDALIER

BOSCH

MANIVELLES

E13 E*Spec Plus BOSCH CX

160 mm crank arms

PLATEAU

E13 E*Spec Plus BOSCH CX

34t, direct mount

CHAINE

SHIMANO XT

12s

CASSETTE

SHIMANO XT

12s, 10-51t

JANTES

Rear: DT SWISS HX1700 Spline - Front: DT SWISS HX1700 Spline

Rear: 27.5", 28h, welded, 30 mm inner width - Front: 29", 28h, welded, 30mm inner width

MOVEUX

Rear: DT SWISS 350 - Front: DT SWISS 350

Rear: 28h, sealed bearings, 24t, e-bike specific - Front: 28h, sealed bearings

RAYONS

DT SWISS Hybrid 1

Straightpull, 2.34/2.0mm, double butted, stainless, with Nyllok, black

PNEUS

Rear: SCHWALBE Big Betty - Front: SCHWALBE Magic Mary

Rear: 27.5" x 2.4", Super Trail, Addix Soft, Tubeless Easy - Front: 29" x 2.4", Super Trail, Addix Soft, Tubeless Easy

TIGE DE SELLE

Fox Transfer Factory

31.6 mm, travel: 125 mm on S, 175 mm on M/L & 200 mm on XL, SHIMANO SL-MT500 remote

SELLE

FIZIK Terra Aion X3

145 mm width, Kium Mobius rails

POIDS

- kg

Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.

PEDALES

Yes

COULEUR

Light Purple / Black

Shiny Finish

ACCESSOIRES

RIDE ALPHA CNC pedals, fork fender, motor protector, chainstay protector, seatstay protector, user manual

*Les spécifications du vélo sont susceptibles d'être modifiées sans préavis.

RECYCLAGE BATTERIE

Partnership with BOSCH

The battery (used up, damaged, defective) must be recycled. Each national distributor is responsible for providing the dealer with a free recycling solution. Applicable laws: Battery Act, Directive 2006/66/EC, BattG in Germany too. Robert Bosch GmbH recommends concluding a contract with a national service provider for returning batteries in each case.

TECH

TYPE DE VELO

E-BIKE ENDURO 29"/27"

CADRE

AL-6061 + AL-6066

POIDS DU CADRE

- kg - With plastic accessories.

DEBATTEMENT ARRIERE

165 mm

ENTRE-AXE / COURSE

230 x 65 mm

COMPATIBLE PIGGY BACK

Yes

BUSELURES AMORTISSEUR

20 x 10 mm front

HAUTEUR DE FOURCHE RECOMMANDEE / MAX

583 mm / 593 mm

DOUILLE DE DIRECTION

Tapered

JEU DE DIRECTION

ZS56 / ZS66

LARGEUR MAXIMALE PNEUS (ETRT0)

65 - 584 mm

STANDARD FREIN A DISQUE

PM160

DIAMETRE MAX DISQUE DE FREIN AR

220 mm

DIAMETRE TIGE DE SELLE / COLLIER DE SELLE

31.6 mm / 34.9 mm

BOITIER DE PEDALIER

BOSCH E-BIKE

ISCG

Yes (BOSCH Standard)

DERAILLEUR AVANT

No

AXE DE ROUE ARRIERE

12 x 148 mm

- Géométrie
- Tailles