

2023

COMMENCAL META POWER TR BOSCH RACE SPARKLY BLUE



SPECS

CADRE META POWER TR BOSCH, 140 mm 29", Alloy 6066, triple butted tubes, T4, T6. Bolu bearings
MOTEUR BOSCH Performance Line CX Max. torque: 85N.m, 250W
BATTERIE BOSCH PowerTube 625 625Wh
BATTERY CHARGER BOSCH 4A Charger Compact size & lightweight
AFFICHAGE BOSCH System Controller
SWITCH BOSCH Mini Remote
AMORTISSEUR ROCKSHOX Super Deluxe Ultimate 210 x 55 mm, LSC, rebound, 2-position adjustment. Spring rates : 350lbs on S / M, 400lbs on L, 450lbs on XL, 2-position adjustment
FOURCHE ROCKSHOX Lyrik Ultimate, 160 mm travel 29", Charger 3 RC2 damper, DebonAir+, LSC, HSC, rebound, Boost (15 x 110 mm), 44 mm offset, 0 Token
JEU DE DIRECTION ACROS ZS56 / ZS66 Alloy cups, sealed bearings
POTENCE RIDE ALPHA 40 EXTERNAL 40 mm extension, 31,8 mm
CINTRE RIDE ALPHA R20 POWER on S - RIDE ALPHA R27 POWER on M / L / XL Internal Di2 cable routing - 31.8 mm, 760 mm width, 20 mm rise, Alloy 6061 on S - 31.8 mm, 780 mm width, 27 mm rise, Alloy 6061 on M / L - 31.8 mm, 800 mm width, 27 mm rise, Alloy 6061 on XL
GRIPS ODI Elite Motion Soft pro compound, single clamp, black
FREINS TRP DH-R Evo 4 pistons
DISQUES TRP R1 220 mm 6-bolt, 2.3 mm width
SHIFTERS SRAM GX Eagle 12s, Single Click
GUIDE CHAÎNE RIDE ALPHA Upper Guide 32-34t
DERAILLEUR SRAM GX Eagle 12s
BOITIER DE PEDALIER BOSCH
MANIVELLES E13 E*Spec Plus Bosch CX 160 mm crank arms
PLATEAU E13 E*Spec Plus Bosch CX 34t, direct mount
CHAÎNE SRAM GX Eagle 12s
CASSETTE SRAM GX Eagle 12s, 10-52t
JANTES Rear: DT SWISS H1900 Spline - Front: DT SWISS H1900 Spline Rear: 29", 28h, sleeved, 30 mm inner width - Front: 29", 28h, sleeved, 30 mm inner width
MOYEURX Rear: DT SWISS 370 - Front: DT SWISS 370 Rear: 28h, sealed bearings, 18t, e-bike specific - Front: 28h, sealed bearings
RAYONS DT SWISS Hybrid 1 Straightpull, 2.34/2.0mm, double butted, stainless, with Nylok, black
PNEUS Rear: MAXXIS DHR II - Front: MAXXIS DHR II Rear: 29"x2.4" WT, 3C Maxx Terra, Exo+ casing, TR - Front: 29"x2.4" WT, 3C Maxx Terra, Exo+ casing, TR
TIGE DE SELLE KS Rage I 31.6 mm, travel: 125 mm on S, 170 mm on M/L, 190 mm on XL, SouthPaw alloy remote
SELLE FIZIK Terra Aidon X5 145 mm width, S-Alloy Mobius rails
POIDS - kg Average weight for S size, without pedals. Weight may differ slightly due to manufacturing tolerances.
PEDALES Yes
COULEUR Dorval Blue Shiny Finish
ACCESSOIRES RIDE ALPHA CNC pedals, motor protector, chainstay protector, seatstay protector, user manual *Les spécifications du vélo sont susceptibles d'être modifiées sans préavis.

RECYCLAGE BATTERIE

Partnership with BOSCH

The battery (used up, damaged, defective) must be recycled. Each national distributor is responsible for providing the dealer with a free recycling solution. Applicable laws: Battery Act, Directive 2006/66/EC, BattG in Germany too. Robert Bosch GmbH recommends concluding a contract with a national service provider for returning batteries in each case.

TECH

TYPE DE VELO E-BIKE TRAIL 29"
CADRE AL-6061 + AL-6066
POIDS DU CADRE - kg - With plastic accessories.
DEBATTEMENT ARRIERE 140 mm
ENTRE-AXE / COURSE 210 x 55 mm
COMPATIBLE PIGGY BACK Yes
BUSELURES AMORTISSEUR 20 x 10 mm / NOTHING
HAUTEUR DE FOURCHE RECOMMANDEE / MAX 566 mm / 576 mm
DOUILLE DE DIRECTION Tapered
JEU DE DIRECTION ZS56 / ZS66
LARGEUR MAXIMALE PNEUS (ETRTO) 65 mm - 622
STANDARD FREIN A DISQUE PM160
DIAMETRE MAX DISQUE DE FREIN AR 220 mm
DIAMETRE TIGE DE SELLE / COLLIER DE SELLE 31.6 mm / 34.9 mm
BOITIER DE PEDALIER BOSCH
ISCG Yes (BOSCH Standard)
DERAILLEUR AVANT No
AXE DE ROUE ARRIERE 12 x 148 mm

- Géométrie
- Tailles