# 2025

COMMERCIAL EDITION 29-in

## SPECS

FRAME
Alloy, 29-in wheel, 150 mm travel

FRONT SUSPENSION
Fox 36 Factory, 29-in wheel, 150 mm travel

REAR SHOCK
Fox Factory, 205 mm x 60 mm

CRANKSET
Shimano Deore M6100, 170 mm

CHAINRING
32-tooth, Shimano Deore

CASSETTE
Shimano Deore M6100, 10-51 tooth

CHAIN
KMC X10EPT, 10-speed

REAR DERAILLEUR
Shimano Deore M6100, SGS

SHIFTERS
Shimano Deore M6100, 10-speed

BRAKES
Shimano Deore M6120, 4-piston, 203 mm rotors

HANDLEBAR
Alloy, 35 mm, 20 mm rise, 800 mm, 10 mm cut

STEM
Alloy, 35 mm

GRIPS
Lock-on

SADDLE
Fabric, 142 mm

SEATPOST
Alloy, 31.6 mm, 125 mm dropper, 400 mm travel

PEDALS
Alloy, 9/16-in

WHEELS
Alloy, 29-in, 30 mm inner width, Shimano Deore M6100 hubs, 32-hole, 1.5-in, 1.5-in, 28-spoke, stainless steel

TIRE SIZE
29 x 2.6-in, 60 TPI

TIRE TYPE
Tubeless, 60 TPI

TIRE PRESSURE
Front: 22 psi, Rear: 24 psi

TIRE LINER
Front

FRONT TIRE
Maxxis Minion DHF

REAR TIRE
Maxxis Minion DHR II

FRONT TIRE COMPOUND
EXO+, TR

REAR TIRE COMPOUND
3C MaxxTerra, EXO+, TR

FRONT TIRE TRACTION
Gravity

REAR TIRE TRACTION
Grip

FRONT TIRE CASING
Folding

REAR TIRE CASING
Folding

## Front Triangle

| | | | |
|---|---|---|---|
| 1 | [illegible] | Front Triangle | 1 |
| 2 | [illegible] | Front Triangle | 1 |
| 3 | [illegible] | Front Triangle | 1 |
| 4 | [illegible] | Front Triangle | 1 |
|